



भारत का राजपत्र

The Gazette of India

असाधारण

EXTRAORDINARY

भाग II—खण्ड 3—उप-खण्ड (ii)

PART II—Section 3—Sub-section (ii)

प्राधिकार से प्रकाशित

PUBLISHED BY AUTHORITY

सं. 1232]

नई दिल्ली, सोमवार, अगस्त 10, 2009/श्रावण 19, 1931

No. 1232]

NEW DELHI, MONDAY, AUGUST 10, 2009/SRAVANA 19, 1931

कृषि मंत्रालय

(कृषि और सहकारिता विभाग)

अधिसूचना

नई दिल्ली, 10 अगस्त, 2009

का.आ. 2073(अ).—केन्द्रीय सरकार, उर्वरक (नियंत्रण)

आदेश, 1985 के खण्ड 20क के अनुसरण में—

- नेशनल फर्टिलाइजर लिमिटेड (एनएफएल);
- श्रीराम फर्टिलाइजर एण्ड केमिकल्स लिमिटेड;
- इन्डो गल्फ फर्टिलाइजर्स;
- टाटा केमिकल्स लिमिटेड;
- चम्बल फर्टिलाइजर एण्ड केमिकल्स लिमिटेड;
- मंगलौर केमिकल्स एण्ड फर्टिलाइजर्स लिमिटेड;

द्वारा विनिर्माण किए जाने वाले नीम विलेपित यूरिया के अन्तिम उर्वरकों की बाबत एक वर्ष की अवधि के लिए जब तक इसे इससे पहले प्रतिसंहरित न कर दिया जाए निम्नलिखित विनिर्देश अधिसूचित करती है :—

नीम विलेपित यूरिया

विनिर्देश :

- | | |
|--|-------|
| (i) भार के आधार पर आर्द्रता का अधिकतम प्रतिशत | 1.0 |
| (ii) भार के आधार पर कुल नाइट्रोजन का न्यूनतम प्रतिशत | 46.0 |
| (iii) भार के आधार पर ब्युरेट का अधिकतम प्रतिशत | 1.5 |
| (iv) भार के आधार पर बेन्जीन विलेय घटक का न्यूनतम प्रतिशत | 0.035 |

कण का आकार—सामग्री का 90 प्रतिशत से अन्तून जो 2.8 मि. मी. भा. मा. छलनी में से छन जाएगा और भार के अनुसार 80 प्रतिशत से अन्तून 1 मि. मी. भा. मा. छलनी पर रह जाएगा ।

[फा. सं. 1-5/2002-उर्वरक विधि]

पंकज कुमार, संयुक्त सचिव

MINISTRY OF AGRICULTURE

(Department of Agriculture and Co-operation)

NOTIFICATION

New Delhi, the 10th August, 2009

S.O. 2073(E).—In pursuance of clause 20A of the Fertiliser (Control) Order, 1985, the Central Government hereby notifies the following specifications in respect of the provisional fertilisers Neem Coated Urea to be manufactured by—

- National Fertiliser Ltd. (NFL);
- Shri Ram Fertiliser and Chemicals Limited;
- Indo Gulf Fertilisers;
- Tata Chemicals Limited;
- Chambal Fertiliser and Chemicals Limited;
- Mangalore Chemicals and Fertilisers Limited;

for a period of one year unless revoked earlier, namely:—

Neem Coated Urea

Specifications:

- | | |
|--|-------|
| (i) Moisture per cent. by weight, maximum | 1.0 |
| (ii) Total nitrogen per cent by weight, minimum | 46.0 |
| (iii) Biuret, per cent. by weight, maximum | 1.5 |
| (iv) Benzene soluble content, percent by weight, minimum | 0.035 |

Particle Size: Not less than 90 per cent of the material shall pass through 2.8 mm IS sieve and not less than 80 per cent by weight shall be retained on 1 mm IS sieve.

[F.No.1-5/2002-Fert. Law]

PANKAJ KUMAR, Jt. Secy.